



Overall Dimensions	
Length	13'-2"
Width	8'-6"
Height to stack top	7'-5"
Weight	19,800 lbs
Engine Specifications	
Type	4 Cyl Turbo Diesel
Cooling	Axial Fan/Air Cooled
Rating	95+ HP / EPA Tier II
Fuel Consumption(Est)	1 gph @ 75% Load
Operating Parameters	
Power Unit	4/All Wheel Drive or Tracked W/ GVWR 38000 lbs +
Operating Min/Max Speed	1 to 5 kph
Maximum Transport Speed	30 kph
Hydraulic Specifications	
Pump Type	60cc Piston PC/LS
Cylinders	12" Stroke w/ Lock Valving
Valving	Manifold Block/Cartridge

Ripper Specifications	
Autofeed Knives	19
Knife Spacing	9 3/4"
Shank Attachment	Single Pin
Maximum Penetration	6"
Depth Control	1/2" or 1" Steps
Disc Specifications	
Disc Spoons	100
Spoon Spacing	7 1/8"
Disc Operating RPM	80 - 100
Disk Torque	1548 ft/lbs (Int)
Maximum Penetration	6"
Surface Displacement	5000sq/ft min
Depth Control	1/2" or 1" Steps
Electrical Control Information	
Wireless Radio Remote Control	
Programable & Adjustable Receiver	
Automatic Disc Depth/Speed Control	
Unitized Central Control Panel	

Unit subject to severe vibration through operational applications. Unit inspection and maintenance must be performed accordingly.

**ROADBADGER™**  
 Corporate Mailing Address:  
 P.O. Box 4244  
 Edmonton, Alberta, Canada T6E 4T2



  
 Designed and Manufactured  
 in North America



**Visit our website at:**  
[www.roadbadger.com](http://www.roadbadger.com)

Tel: +1-780-433-4322  
 Fax: +1-780-665-7269  
 E-Mail: [sales@roadbadger.com](mailto:sales@roadbadger.com)